

PREPARE TO BE FLOORED.

Ash Traditional



Creamy white sapwood to rich brown heartwood.

Color can vary from a light gray-brown to creamy white in the sapwood to a deep brown heartwood. Grain is long and can be sometimes confused with oak grain. A very hard wood, Ash is excellent for virtually any application.

Flooring/Paneling

Great on walls and ceilings, perfect for floors!

Random Widths	3"-6", 5"-7"
Specified Widths	5"
Thickness	3/4", 5/8", or 1/2"
Lengths	2-12' Random or Specified Lengths
Milled Profile	Tongue and Groove, Square or Shiplap
Edges	Square or Pillowed
Finish	Pre Finished or Unfinished
Fire Retardant	Optional

Stair Treads and Parts

We'll glue, sand and cut to size to your design specifications, and shape your treads with a variety of edges.

Finish Pre Finished or Unfinished

Wood Tops

Countertops, table tops, and bar tops all shaped to suit with a variety of edges.

Thickness	1 1/2"
Edges	Eased or Milled Profile
Finish	Pre Finished or Unfinished

Cabinet Lumber

Kiln dried, rough planed and straight line ripped on the inch, same widths as flooring/paneling.

Thickness 4/4, 8/4



Elmwood Reclaimed Timber

22701 S. Peculiar Drive

Peculiar, Missouri 64078

elmwoodreclaimedtimber.com

(800) 705-0705 toll free

(816) 779-7300 phone

(816) 779-7307 fax